



Short form Characteristics

ELECTRICAL

Power	12W
Input Voltage	24V
Input Voltage range	22-27V
Type of current	DC
Over temp.protection	150°C
Energy class	A+

PHOTOMETRICAL

Flux nominal	1680lm
Efficiency	140lm/W
Number of LED's	24
Rendering Index	Ra80
SDCM (Mac Adam)	3
Spread angle lens	130°
Colour temperatures	2700K 3000K 4000K 5700K

ENVIRONMENTAL

Temperature range	-40°C to 65°C (Absolute max .temp Tc 65°)
Relative Humidity	10-75%
Ambient air pressure	500-1060 hPa

MECHANICAL

Module dimension	Diam.50mm
Weight	14 gr
Assembly holes	na
Connection	terminals

LIFE LENGHT

Life lenght L70B10	>50 000h
--------------------	----------



Coding

KA.nn.ww.v.k.s

NN	Numero led
WW	Potenza
Voltage	(1) 110V (3) 230V (4) 240V (6) 24V
K	(2) 2700K (3) 3000K (4) 4000K (5) 5700K
S	(C) Cob (Q) Quadro (R) Rotondo (S) Lineare (Q) Corona (K) Kobra

Article name and version

ARTICLE NAME	POWER	VOLTAGE	LED	CCT
KA241262R	12	24	24	2700
KA241263R	12	24	24	3000
KA241264R	12	24	24	4000
KA241265R	12	24	24	5700

